

### Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

#### Listing of Claims:

1.-23. (canceled)

24. (currently amended) A method for displaying a cursor on a display of an electronic device, the method comprising the steps of:

concurrently displaying the cursor and only a displayed part of a virtual view on the display of the electronic device ~~such that the cursor is continuously visible when the display displays any part of the virtual view~~, wherein the virtual view is larger than a size of the display and comprises an entire spatially arranged data set in which a user of the electronic device navigates, and the cursor is continuously visible on the display at a cursor location so that the deviation of the cursor from the center of the display is proportional to the deviation of the location of the concurrently displayed part of the virtual view from an origin of the virtual view;

~~moving the displayed part of the virtual view in response to user scrolling actions[[:]],~~  
changing the displayed part of the virtual view and moving the cursor, wherein said moving the cursor comprises

~~determining continuously a relation between the cursor location on the display and the location of the displayed part of the virtual view within the whole virtual view so that the cursor location on the display reflects the location of the displayed part of the virtual view in proportion to the whole virtual view, and so that the deviation of the cursor from a center of the displayed part of the virtual view is proportional to the deviation of the displayed part from an~~ in relation to the origin of the virtual view; and

~~changing, in accordance with the determined relation, the location of the cursor in response to the user scrolling actions during the step of moving~~ changing the displayed part so that the deviation of the cursor from the center of the display is always proportional to the deviation of the location of the concurrently displayed part of the virtual view from the origin of the virtual view,

wherein the cursor is always visible on the display when any part of the virtual view is displayed on the display and the cursor location on the display provides, to a user of the electronic device, continuous navigation information for scrolling within the whole virtual view.

25. (currently amended) The method according to claim 24, wherein said step of ~~changing~~ moving the cursor comprises moving the cursor in the same direction as the virtual view is scrolled.

26. (currently amended) The method according to claim 24, wherein the relation between the deviation of the cursor from a center of the displayed part of the virtual view and the deviation of the displayed part from ~~an~~ the origin of the virtual view is linear.

27. (currently amended) The method according to claim 24, wherein the step of ~~moving~~ changing the displayed part includes changing the orientation of the electronic device and changing the view on the display in response to the changed orientation.

28. (previously presented) The method according to claim 24, wherein the cursor, at least one of the displayed part of the virtual view and the virtual view have the same origin.

29. (currently amended) The method according to claim 24, wherein the relation between the deviation of the cursor from a center of the displayed part of the virtual view and the deviation of the displayed part from ~~an~~ the origin of the virtual view is non-linear.

30. (currently amended) The method according to claim 24, wherein said step of ~~moving~~ changing the displayed part comprises changing the location within the virtual view of the displayed part in response to the user scrolling actions.

31. (currently amended) An electronic device for displaying a cursor on a display of the electronic device, the electronic device comprising:

a processor;

a memory coupled to the processor, the memory comprising a virtual view suitable for conveying information to the user of the electronic device, the virtual view comprising an entire spatially arranged data set in which a user of the electronic device navigates;

a display coupled to the processor concurrently displaying a cursor and only a displayed part of the virtual view, wherein the virtual view is larger than a size of the display, and the cursor is continuously visible on the display at a cursor location so that the deviation of the cursor from the center of the display is proportional to the deviation of the location of the concurrently displayed part of the virtual view from the origin of the virtual view;

view control means with which the location within the virtual view of the displayed part of the virtual view on the display is moved in response to scrolling actions performed by a user of the electronic device;

~~the display displaying a cursor such that the cursor is continuously visible when the display displays any part of the virtual view, wherein a~~ comprising means for moving the location of the cursor on the display is in a relation to the location of the displayed part of the virtual view within the whole virtual view so that the cursor location on the display continuously reflects indicates the location of the displayed part of the virtual view in proportion to the whole virtual view during the movement of the location of the displayed part of the virtual view in response to the scrolling actions, and so that [[a]] the deviation of the cursor from a center of the displayed part of the virtual view display is proportional to the deviation of the displayed part from the original origin of the virtual view; and

~~wherein the display comprises means for changing, in accordance with the relation, the location of the cursor during the user scrolling actions when the display is changed by the view control means, wherein the cursor is always visible on the display when any part of the virtual view is displayed on the display such that the cursor location provides, to a user of the electronic device, continuous navigation information for scrolling within the whole virtual view.~~

32. (previously presented) The electronic device according to claim 31, further comprising a browse lock switchable between an on state and an off state, the displayed part being static when the browse lock is in the off state and being changeable when the browse lock is in the on state so that the location of the cursor on the display and the location of the displayed

part of the virtual view within the whole virtual view is changed during the user scrolling actions in accordance with the relation in the on state.

33. (previously presented) The electronic device according to claim 31, wherein the view control means include at least one of motion control means, a scroll bar, or a mouse.

34. (previously presented) The electronic device according to claim 31, wherein the electronic device is a mobile phone.

35. (previously presented) The electronic device according to claim 31, wherein the electronic device is one of a Personal Digital Assistant (PDA), remote control, gaming console, web tablet, wireless device, mobile camera or internet appliance.

36. (previously presented) The electronic device according to claim 31, wherein the cursor, the displayed part of the virtual view and the virtual view are configured to have the same origin.